

Kozane[®] INVICTA Original

Art. no. 500.2019

The new Kozane[®] INVICTA range features outstanding tear and abrasion resistance, with added cut and puncture resistance.



EN 388:2016 6.1 Abrasion	Level 4
EN 388:2016 6.2 Blade cut resistance	Level X*
EN 388:2016 6.4 Tear resistance	Level 4
EN 388:2016 6.5 Puncture resistance	Level 4
EN 388:2016 6.3 Cut resistance method (EN ISO 13997:1999)	Level B

*x stands for not tested. As per clause 6.2.6 of EN 388:2016 for materials dulling the blades, if after the first sequence the number of cycles Cn+1 is greater than 3 times Cn in one of the tested specimen, the EN ISO 13997:1999 Cut resistance method as per clause 6.3 shall be performed and this method becomes the reference test method for the assessment of the protection against cut risks.

PATENT PENDING

Applications:

- Tear-resistant clothing and bedding for mental health and prisons/corrections.
- Additional applications, not limiting to: footwear, luggage, upholstery etc.

Weight / surface density	470g/m ²
Roll width	1.87m
Colour	Black
Safety and care instructions	100 E 🖄 🖻 🕑



FEARLESS PERFORMANCE*

Granberg AS | Bjoavegan 1442 | 5584 Bjoa | Norway t. +47 53 77 53 00 | e. post@granberg.no Eve Ichim - Global Business Development Manager Kozane® High-Performance Fabrics | m. +44(0)7599 546 566 | e. eve.ichim@granberg.no