

Kozane® Cut-Resistant Chaps

Art. no. 708-05

Designed to offer the highest level of cut resistance on the legs, with adjustable straps. Suitable for work environments where there is a risk of cuts and lacerations to the front of the legs. Manufactured using our Kozane® Extreme cut-resistant fabric (article number 500.3100).





EN 388:2016 6.1 Abrasion	Level 3
EN 388:2016 6.2 Blade cut resistance	Level X*
EN 388:2016 6.4 Tear resistance	Level 4
EN 388:2016 6.5 Puncture resistance	Level 4
EN 388:2016 6.3 Cut resistance method (EN ISO 13997:1999)	Level F
ANSI ASTM F2992-15	Cut A8 (Cut Score: 5,215g)

 $^{*}x$ stands for not tested. As per clause 6.2.6 of EN 388:2016 for materials dulling the blades, if after the first sequence the number of cycles Cn+1 is greater than 3 times Cn in one of the tested specimen, the EN ISO 13997:1999 Cut resistance method as per clause 6.3 shall be performed and this method becomes the reference test method for the assessment of the protection against cut risks.

PATENT PENDING



Applications:

✓ Glass handling

Transportation and manufacturing

Paper/pulp processing

General manufacturing

Size	One Size, Adjustable	
Colour	Black	
Safety and care instructions		