

Kozane[®] Invicta Art. No. 500.2019

Kozane[®] Invicta features outstanding tear and abrasion resistance, with added cut and puncture resistance.



| EN 388: 2016 6.1 Abrasion | Level 4 |
|--|----------|
| EN 388: 2016 6.2 Blade cut resistance | Level X* |
| EN 388: 2016 6.4 Tear resistance | Level 4 |
| EN 388: 2016 6.5 Puncture resistance | Level 4 |
| EN 388: 2016 6.3 Cut resistance method (EN ISO 13997:1999) | Level B |

*x stands for not tested. As per clause 6.2.6 of EN 388:2016 for materials dulling the blades, if after the first sequence the number of cycles Cn+1 is greater than 3 times Cn in one of the tested specimen, the EN ISO 13997:1999 Cut resistance method as per clause 6.3 shall be performed and this method becomes the reference test method for the assessment of the protection against cut risks.

Potential applications:

- Tear-resistant clothing and bedding for mental health and prison/corrections
- Extremely durable footwear, luggage, upholstery
- ✓ Abrasion resistant protective motorcycle apparel
- Reinforcements (i.e. knees and elbows) for puncture, tear and abrasion resistance

Sectors:

Sports and Leisure, Healthcare, Prisons and Corrections, Security/Army

| Weight | 470 g/m2 |
|-------------|---------------|
| Roll width | 1.87m |
| Roll length | 18m |
| Colour | Black or Grey |

GranberG

FEARLESS PERFORMANCE*

Granberg AS | Bjoavegan 1442 5584 Bjoa | Norway t: +47 53 77 53 00 e: post@granberg.no Eve Lamb – Global Business Development Manager Kozane® High-Performance Fabrics | m: +44 (0) 7599 546 566 e: eve.lamb@granberg.no